



XC-NT200 Hardened ADSL Modem



FEATURES

- Full-rate ADSL and G.lite operation
- Integrated 10/100 Ethernet MAC
- Secure
- Easy installation
- Uses existing site phone cabling

Description

The NT 200 ADSL modem is the choice for value and performance in the industrial broadband marketplace. Because of its solid list of features, it is the perfect choice for those difficult installations where environmental conditions are challenging.

The NT200 modems are versatile and come in several configurations and models. All are capable of supporting faster ADSL standards like ADSL2 and ADSL2+ with software upgrades.

The NT200 Ethernet Bridge has “plug and play” simplicity, it's easy to install and dramatically lowers deployment costs. No site dependent software is required.



NT200

Hardened ADSL Modem

Product Specifications

- **Dimensions**
 - Height: 1.21 in. (3.07 cm)
 - Width: 4.0 in. (10.16 cm)
 - Depth: 3.88 in. (9.86 cm)
- **Weight**
 - Approx 14.0 oz. (.40 kg)
- **Environmental**
 - Temperature: -40°C to +65°C (-40°F to 149°F)
 - Humidity: 10- 95%, non-condensing
- **Power Supply**
 - 120 VAC (10%) to 10.5 VDC
- **Power Consumption**
 - Less than 3 watts typical, from 120 VAC
- **LED Indicators**
 - Power
 - Ready
 - Link
 - Activity
- **Connectors**
 - Power: Barrel connector
 - Line (DSL): 4-pin (RJ-11) modular jack
 - Ethernet: 8-pin (RJ-45) modular jack
- **Standards**
 - ANSI T1.413 issue 2
 - ITU G.992.1 (G.DMT)
 - ITU G.992.2 (G.lite)
 - ITU G.992.3 (ADSL2 DMT)
 - ITU G.992.4 (ADSL2 G.lite)
 - ITU G.992.5 (ADSL2+)
- **Certifications**
 - EMC FCC, Part 15 Class B
 - UL 60950, 3rd Edition
 - CAN/CSA-22.21 60950
 - UL
 - CSA
 - ACTA 968-A
 - Industry Canada CS03

Minimum System Requirements for 10/100 Base-T/Ethernet

Operating system that supports TCP/IP over Ethernet
10/100 Base-T Network Interface Card (NIC)

Specifications subject to change without notice

GDI Communications LLC

PO Box 1330, Verdi, NV 89439

Ph: 775-345-8000 Fax: 775-345-8010 E-mail: sales@sgdi.net

NT200-100808